

MODEL			Space 1	
MAXIMUM POWER	LINE CONDITIONER SYSTEM		1,000~2000 W (UPON USAGE OF THE POWER ISOLATOR SYSTEM)	
	POWER ISOLATOR SYSTEM		1,000 W	
	TOTAL		2,000 W	
INPUT				
VOLTAGE			220~240 V	
FREQUENCY			50 Hz	
AC POWER CORD	TYPE		PVC INSULATION, COMPLY TO UL, CSA STANDARD	
	WIRE SIZE x LENGTH		14 AWG x 2.5 M	
PLUG			3 POLE NEMA 5-15P TYPE	
OUTPUT				
VOLTAGE			220~240 V	
LINE CONDITIONER				
TRANSIENT VOLTAGE SURGE SUPPRESSION			VARISTOR	
RFI AND EMI FILTER			X2, Y2 CAPACITOR, POWER CAPACITOR, TOROIDAL COIL	
HIGH SURGE AND LIGHTNING PROTECTION			LIGHTNING GAS ARRESTER NOMAL IMPULSE DISCHARGE CURRENT 5 kA AT 8/20 μ s SINGLE IMPULSE DISCHARGE CURRENT 10 kA AT 8/20 μ s	
RECEPTACLE	ISOLATED GROUND NEMA 5-20R	TOTAL	FILTER SYSTEM	ISOLATED SYSTEM
		6 OUTLETS	2 OUTLETS	4 OUTLETS
PROTECTION SYSTEM				
OVERLOAD AND OUTPUT SHORT CIRCUIT PROTECTION			FUSE	
DISPLAY				
OPERATION ON STATUS			BLUE LED AT POWER IS LIGHT	
GROUNDING SYSTEM OF INPUT POWER STATUS			BLUE LED AT GROUND IS LIGHT	
GENERAL				
OPERATION ON/OFF			POWER SWITCH	
STRUCTURE				
DIAL			ANODIZED ALUMINUM	
BODY			GALVANIZED SINK METAL 1.2 mm WITH SPECIAL GRADE COLOR COATING	
COVER			ALUMINUM 1.5 mm WITH SPECIAL GRADE COLOR	
NATURAL RUBBER BASE			SOFA, EPDM/80	
SCREWS AND NUTS			STAINLESS STEEL	
WIRING			THE ALPHABHRET DIRECTION WITH THE STAR CIRCUIT SYSTEM TO EACH RECEPTACLE	
PHISICAL				
AMBIENT TEMPERATURE			0~50 $^{\circ}$ C	
RELATIVE HUMIDITY			0~95 %	
DIMENSION (W x H x D)			305 x 210 x 270 mm	
NET WEIGHT			25 kg	

Specifications are subject to change without prior notice. This item can change by customer's requirement.

NUMBER : CTSpace1 ENO

SILICON POWER SUPPLY Co., Ltd.

455/13-16 Soi Phibunuppatham, Latphrao Road, Samsennok, Huaykwang, Bangkok 10320

TEL: 0-2275-1182, 0-2275-1275, 0-2275-7161, 0-2276-9973 FAX: 0-2275-7309 10320

Website: www.sidital.com

Website: www.siliconthai.com

E-mail: info@siliconthai.com

ISO 9001:2000 Certified